

```
tclsh
puts [ open "flash:BASE.CFG" w+ ] {
hostname DLS1
ip domain-name CCNP.NET
no ip domain lookup
interface range f0/1-24 , g0/1-2
shutdown
exit
vtp mode transparent
line con 0
no exec-timeout
logging synchronous
exit
end
}
Tclquit
```

```
tclsh
puts [ open "flash:reset.tcl" w+ ] {
typeahead "\n"
copy running-config startup-config
typeahead "\n"
erase startup-config
delete /force vlan.dat
delete /force multiple-fs
ios_config "sdm prefer dual-ipv4-and-ipv6 routing"
typeahead "\n"
puts "Reloading the switch in 1 minute, type reload cancel to halt"
typeahead "\n"
reload in 1 RESET.TCL SCRIPT RUN
}
tclquit
```

```
tclsh
puts [ open "flash:reset.tcl" w+ ] {
typeahead "\n"
copy running-config startup-config
typeahead "\n"
erase startup-config
delete /force vlan.dat
delete /force multiple-fs
ios_config "sdm prefer lanbase-routing"
typeahead "\n"
puts "Reloading the switch in 1 minute, type reload cancel to halt"
typeahead "\n"
reload in 1 RESET.TCL SCRIPT RUN
}
tclquit
```